# **General Specifications**

### **Engine**

Engine Type 4-stroke, 4-cylinder, DOHC, Liquid cooled, 16-Valve Displacement

636 cc

Bore x Stroke 68.0 x 43.8 mm

Compression Ratio 12.9:1

Carburetor

DFI w/Keihin 38mm Throttle Bodies Ignition System Battery & Coil, TCBI w/Digital Advance

Cylinder Number Method Left to Right: 1-2-3-4

Firing Order 1-2-4-3

Min 91 Research/87 Avg. Oct. Unleaded OK Fuel

50% distilled water /50% ethylene glycol base antifreeze. Coolant

— Capacity N/A — Level N/A

## **Transmission**

Clutch Type Transmission	Wet, Multi-disc 6-speed, Return shift
Gear Ratios — 1st	2.92 (38/13)
— 2nd	2.06 (37/18)
— 3rd	1.66 (33/21)
— 4th	1.45 (29/20)
— 5th	1.27 (28/22)
— 6th	1.15 (30/26)
Primary Ratio	1.891 (87/46)
Final Ratio	2.865 (43/15)
Overall Ratio (Top Gear)	6.255

### Chassis

Wheelbase Seat Height		1,370 mm (54.7 in.) 820 mm (32.3 in.)
Ground Clearance		120 mm (4.7 in.)
Dry Weight		164 kg (362 lb.)
Curb Weight		Front 95 kg (210 lb.)
		Rear 97 kg (214 lb.)
Fuel Tank Capacity		17.0 liter (4.5 gal.)
Tire Size	— Front	120/65 ZR17
	— Rear	180/55 ZR17
Brake Type	— Front	Dual Hydraulic Disc
	— Rear	Single Hydraulic Disc
Brake Size	— Front	268 mm Effective Diameter
	— Rear	184 mm Effective Diameter
Wheel Travel	— Front	120 mm (4.7 in.)
	— Rear	135 mm (5.3 in.)

## **Model Identification**

Year & Model '06 ZX636D6F:NINJA ZX-6R 1. Metallic Titanium (740) Color VIN Range JKBZXJD1**✓** 6A000001 ~ Engine No. Range ZX636CE000001 — Engine No. Location FR top crankcase

## **Tuning Specifications**

### **Engine**

Valve Clearance (Cold) Intake: 0.11-0.19 mm Exhaust: 0.22-0.31 mm — Adjustment Method Shim under bucket Compression Pressure 225 psi

Spark Plug

NGK CR9E — Gap 0.7-0.8 mm

Ignition Timing— Idle 12.5° BTDC at 1,300 rpm (US)

— Full 35° at 4,600 rpm  $1300 \text{ rpm } \pm 50$ Idle Speed

API SE, SF, SG/SH or SJ with JASO MA SAE 10W40 Engine Oil

— Capacity 4.0 liter (4.2 gt.)

On center stand, wait 5 min., middle of window — Level

426 cc

#### Chassis

Showa SS05 SW Fork Oil

— Capacity Tire Pressure (Cold)

36 psi — Front — Rear 42 psi